

## Fristam FKL Positive Displacement Pump Specifications by Model

Model		15	20	25	50	75	150	250	400	600
<b>Displacement</b> (at max rpm)	gal/rev	0.0155	0.032	0.056	0.096	0.156	0.259	0.54	0.74	2.24
	gpm	15.5	25.6	33.6	57.6	93.6	155	324	444	896
	l/m	58.7	96.9	127.2	218	354	588	1226	1681	3392
	m <sup>3</sup> /hr	3.5	5.8	7.6	13.1	21.3	35.3	73	100	203
<b>Speed (max)</b>	rpm	1000	800	600	600	600	600	600	600	400
<b>Pressure (max)</b>	psi	200	200	300	500	500	500	500	300	300
	bar	14	14	21	35	35	35	35	21	21
<b>Fittings</b>										
Housing		1.5" clamp	1.5" clamp	1.5" clamp	2.5" clamp	2.5" clamp	3" clamp	4" clamp	6" flange	6" flange
Seal Flush Thread		1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	M10 x 1.5
<b>Weight</b> (complete pump)	lbs	75	75	104	135	360	451	744	950	1680
	kg	34	34	47	61	163	205	338	431	762
<b>Special Options</b>										
Rectangular Inlet		N/A	N/A	N/A	Yes	Yes	Yes	Yes	Yes	N/A
O-Ring Seal		Yes	Yes	Yes	Yes	Yes	Yes	Yes	N/A	N/A